

BOSTIK SAFE SEAL GREY Revision Number 2

Revision date 29-Jul-2019 Supersedes Date: 26-Mar-2018

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name BOSTIK SAFE SEAL GREY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.

Uses advised against No information available.

1.3. Details of the supplier of the safety data sheet

 Company Name
 Manufacturer

 Bostik New Zealand Limited
 Bostik GmbH

19 Eastern Hutt Road Wingate, An der Bundesstrasse 16
Lower Hutt, New Zealand 33829 Borgholzhausen, Germany

Tel: 04-567 5119 Tel: +49 (0) 5425 / 801 0 Fax: 04-567 5412 Fax: +49 (0) 5425 / 801 140

1.4. Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622

+64 4 917 9888

Poison Centre: 0800 764 766

E-mail address SDS.AP@Bostik.com

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Skin corrosion/irritation	Category 3 (6.3B)
Skin sensitization	Category 1 (6.5B)

Classification in parenthesis is applicable for New Zealand Hazard Classification

2.2. Label Elements



Signal word Warning

Hazard statements

H316 - Causes mild skin irritation

H317 - May cause an allergic skin reaction

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

Prevention

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P272 - Contaminated work clothing should not be allowed out of the workplace

BOSTIK SAFE SEAL GREY Revision Number 2

Revision Number 2 Supersedes Date: 26-Mar-2018

Revision date 29-Jul-2019

P280 - Wear protective gloves

Skin

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P363 - Wash contaminated clothing before reuse

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other Hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	CAS No.	Weight-%
Octadecanoic acid, 12-hydroxy-, reaction products	100545-48-0	1 - <3
with ethylenediamine		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	0.1- <1
3-(Triethoxysilyl) propylamine	919-30-2	0.1- <1
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0.1- <1

^{***} Any remaining ingredients are not hazardous

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Remove

contaminated clothing and shoes.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

Skin contact Wash off immediately with soap and plenty of water. In the case of skin irritation or

allergic reactions see a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Hold eyelids apart and consult an

physician.

Ingestion If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label. If swallowed, rinse mouth with water (only if the person is conscious).

Self-protection of the first aider First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing.

4.4. Reference to Other Sections

Reference to other sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Section 11:

BOSTIK SAFE SEAL GREY Revision Number 2

TOXICOLOGY INFORMATION.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2). Extinguishing powder. Water spray or fog. Alcohol resistant foam.

Large fire When a large quantity of this material is involved in a major fire, consider an initial

evacuation distance of 300 meters (1000 feet) in all directions.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of toxic/corrosive gases and vapors. Carbon monoxide. Carbon dioxide (CO2). Halogenated hydrocarbons. Nitrogen oxides (NOx).

Revision date 29-Jul-2019

Supersedes Date: 26-Mar-2018

Hazardous combustion products

Carbon monoxide. Carbon dioxide (CO2).

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

In the event of fire, wear self-contained breathing apparatus. Do not allow run-off from

fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protection equipment. Avoid contact with skin, eyes or clothing. Do not

touch or walk through spilled material.

6.2. Environmental precautions

Environmental precautions Do not allow to enter into soil/subsoil. Prevent entry into waterways, sewers, basements

or confined areas.

6.3. Methods and material for containment and cleaning up

Methods for containment Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and place in container for disposal according to local /

national regulations (see Section 13).

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal. Soak up with inert

absorbent material.

6.4. Reference to other sections

Reference to other sections Section 7: HANDLING AND STORAGE

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Fire prevention measures. No special measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Do not eat, drink or smoke when using this product. Wash hands thoroughly after General hygiene considerations

BOSTIK SAFE SEAL GREY Revision Number 2

Revision Number 2 Supersedes Date: 26-Mar-2018

handling. Take off contaminated clothing and wash before reuse. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or

Revision date 29-Jul-2019

clothing.

Storage Conditions Keep away from food, drink and animal feeding stuffs. Protect from moisture. Keep/store

only in original container. Protect from sunlight. Store in a well-ventilated place. Keep at temperatures between 41 and 95 °F. Keep container tightly closed and dry. Product

cures with moisture.

Incompatible materials Water

7.3. Specific end use(s)

Specific Use(s) Sealant.

Other information No information available.

7.4. References to Other Sections

Reference to other sections Section 13: DISPOSAL CONSIDERATIONS. Section 10: STABILITY AND REACTIVITY.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL)No information available

Predicted No Effect Concentration No information available

(PNEC)

OTHER INFORMATION Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

PPE - Personal Protection Equipment

Respiratory protection

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable protective clothing. No special technical protective measures are

necessary under normal conditions.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only

depend on the material, but also on further marks of quality and various manufacturers. No protective equipment is needed under normal use conditions. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask,

or for short periods of work, a combination of professional filter is recommended. **General hygiene considerations**Do not eat, drink or smoke when using this product. Wash hands thoroughly after

handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and

wash before reuse.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

BOSTIK SAFE SEAL GREY Revision Number 2

Revision Number 2 Supersedes Date: 26-Mar-2018

Revision date 29-Jul-2019

_

Appearance Paste Color Gray

Odor Slight Characteristic
Odor threshold No information available

Property Values Remarks • Method

pHNo data availableNot applicableMelting point / freezing pointNo data availableNot applicableBoiling point / boiling rangeNo data availableNot applicableFlash pointNo data availableNot applicable

Evaporation rateFlammability (solid, gas)
No data available
No data available

Flammability Limit in Air

Upper flammability or explosive No data available limits

Lower flammability or explosive No data available

limits

Vapor pressure < 1100 hPa @ 50 °C

Vapor density No data available

Relative density 1.45 - 1.55 None known

Water solubility
Solubility(ies)
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No data available
No data available
No data available
No data available

Dynamic viscosity 7000 - 13000 Pa.s Spindle 4 @ 1 rpm @ 23 °C

Explosive propertiesNo information available **Oxidizing properties**No information available

9.2. Other information

Softening PointNo information availableMolecular weightNo information availableSolvent content (%)No information availableSolid content (%)No information available

Density ca. 1.5 g/cm³ @20°C

Bulk density

No information available

VOC Content (%)

No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None known.

Hazardous polymerization None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Extremes of temperature and direct sunlight. Keep from freezing.

Product cures with moisture.

10.5. Incompatible materials

Incompatible materials Water.

BOSTIK SAFE SEAL GREY

Revision Number 2

Revision date 29-Jul-2019

Supersedes Date: 26-Mar-2018

10.6. Hazardous decomposition products

Hazardous decomposition

None under normal use conditions.

products

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Acute Toxicity

Product Information

InhalationBased on available data, the classification criteria are not met.Eye contactBased on available data, the classification criteria are not met.Skin contactBased on available data, the classification criteria are not met.IngestionBased on available data, the classification criteria are not met.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0	LD50 >2000 mg/kg (Rat)	•	LC50 =5.05 mg/kg (Rat)
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	LD50 (rat)> 2000 mg/kg OECD 423	LD50 (rat) > 3 170 mg/kg OECD 402	= 500 mg/m³ (Rat) 4 h
3-(Triethoxysilyl) propylamine 919-30-2	LD50 = 1490 mg/kg (Rat, female) EPA OTS 798.1175	LD50 = 4075 mg/kg (Rabbit) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rat (Vapour)
N-(3-(trimethoxysilyl)propyl)ethylen ediamine 1760-24-3	LD50 = 2295 mg/kg (rat) EPA OPPTS 870.1100	LD50 > 2000 mg/kg (rabbit) EPA OPPTS 870.1200	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met. **Serious eye damage/eye irritation**Based on available data, the classification criteria are not met.

Sensitization May produce an allergic reaction.

Germ cell mutagenicityBased on available data, the classification criteria are not met. **Reproductive toxicity**Based on available data, the classification criteria are not met.

STOT - single exposure
STOT - repeated exposure
Target organ effects

No information available.
No information available.
Eyes, Lungs, retina, Skin.

Aspiration hazard Not applicable.

Carcinogenicity Based on available data, the classification criteria are not met.

IARC (International Agency for

Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity

Product Information

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Component Information

Data obtained on the component(s) include

Chemical name	Algae/aquatic plants	Fish	Crustacea
---------------	----------------------	------	-----------

BOSTIK SAFE SEAL GREY Revision Number 2

evision Number 2 Supersedes Date: 26-Mar-2018

Revision date 29-Jul-2019

	_	_	
Octadecanoic acid, 12-hydroxy-,	EL50 (72h) >100 mg/L Algae	LL50 (96h) >10mg/L Fish	EL50 (48h) >10mg/L Daphnia
reaction products with	(Pseudokirchneriella subcapitata)	(Onchohynchus mykiss)	(Daphnia magna)
ethylenediamine			
100545-48-0			
Bis(2,2,6,6-tetramethyl-4-piperidyl)		LC50 (96h) = 5.29 mg/l (Oryzias	LC50 48Hr 8.58 mg/l (Daphnia
sebacate	(Pseudokirchnerella subcapitata)	latipes)	magna)
52829-07-9			
3-(Triethoxysilyl) propylamine	EC50 (72h) >1000 mg/L Green	LC50 (96h) >934 mg/L Fish	EC50 (48h) =331 mg/L Daphnia
919-30-2	algae (desmodesmus subspicatus)	(Brachydanio rerio) (OECD TG	magna (OECD TG 202)
	(OECD TG 201)	203)	
N-(3-(trimethoxysilyl)propyl)ethylen	-	LC50 (96H) =597 mg/L Fish (Danio	EC50 (48h) =81mg/L Daphnia
ediamine		rerio)Semi-static	magna Static
1760-24-3		·	-

12.2. Persistence and degradability

No information available.

Component Information			
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)		
Method	Exposure time	Value	Results
OECD Test No. 303: Simulation	28 days	Total organic carbon (TOC)	24 % Moderate
Test - Aerobic Sewage Treatment	·		
A: Activated Sludge Units; B:			
Biofilms			

12.3. Bioaccumulative potential

There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	0.35	-
3-(TriethoxysilyI) propylamine 919-30-2	1.7	3.4
N-(3-(trimethoxysilyl)propyl)ethylenediami ne 1760-24-3	-0.3	-

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0	The substance is not PBT / vPvB
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	The substance is not PBT / vPvB
3-(TriethoxysilyI) propylamine 919-30-2	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	The substance is not PBT / vPvB

12.6. Other adverse effects

No information available.

Section 13: DISPOSAL CONSIDERATIONS

BOSTIK SAFE SEAL GREY Revision Number 2

Revision Number 2 Supersedes Date: 26-Mar-2018

13.1. Waste treatment methods

Waste from residues/unused

products

Disposal should be in accordance with applicable regional, national and local laws and

Revision date 29-Jul-2019

regulations.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Section 14: TRANSPORT INFORMATION

 IMDG
 Not regulated

 IATA
 Not regulated

 ADR
 Not regulated

Section 15: REGULATORY INFORMATION

National Regulations

ERMA Group HSR002670

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 29-Jul-2019

Revision note SDS sections updated, 3, 8, 11.

Training Advice When working with hazardous materials, regular training of operators is required by law

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet