

BOSTIK WALLBOARD GOLD ADHESIVE

Version 2

Revision Date 19-Apr-2017 Supersedes Date: 05-Sep-2016

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product NameBOSTIK WALLBOARD GOLD ADHESIVEPure substance/mixtureMixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Adhesives.
Uses Advised Against	No information available.

1.3. Details of the supplier of the safety data sheet

Company Name Bostik New Zealand Limited 19 Eastern Hutt Road Wingate, Lower Hutt, New Zealand Tel: 04-567 5119 Fax: 04-567 5412 Bostik New Zealand Limited 19 Eastern Hutt Road Wingate, Lower Hutt, New Zealand Tel: 04-567 5119 Fax: 04-567 5412

1.4. Emergency telephone number

Emergency	Telephone
-----------	-----------

E-mail address

SDS.AP@Bostik.com

Poison Centre : 0800 764 766

24 Hr: 0800 243 622

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture

Aspiration toxicity	Category 1 (6.1E g)
Skin Corrosion/Irritation	Category 2 (6.3A)
Reproductive toxicity	Category 2 (6.8B)
STOT - Single Exposure	Category 3 (^f)
Specific target organ toxicity (repeated exposure)	Category 2 (6.9B)
Acute aquatic toxicity	Category 2 (9.1D)
Chronic aquatic toxicity	Category 3 (9.1C)
Flammable Liquids	Category 2 (3.1B)

Classification in parenthesis is applicable for New Zealand Hazard Classification

ERMA Group

HSR002667

2.2. Label Elements

BOSTIK WALLBOARD GOLD ADHESIVE

Version 2

Revision Date 19-Apr-2017 Supersedes Date: 05-Sep-2016



BOSTIK WALLBOARD GOLD ADHESIVE

Version 2

Precautionary Statements - Disposal

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards

· May be harmful if swallowed

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	CAS No.	Weight-%
Toluene	108-88-3	40 - <80
Cyclohexane	110-82-7	1 - <3
Zinc oxide	1314-13-2	0.1- <1
Tall oil rosin	8052-10-6	0.1- <1
Hexane	110-54-3	0.1- <1
4-tert-Butylphenol	98-54-4	0.1- <1

*** Any remaining ingredients are not hazardous

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If medical advice is needed, have product container or label at hand.	
Inhalation	Remove to fresh air.	
Skin Contact	Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention.	
Eye contact	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.	
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.	
Self-protection of the First Aider	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.	
4.2. Most important symptoms and	d effects, both acute and delayed	
Symptoms	None known.	
4.3. Indication of any immediate m	nedical attention and special treatment needed	
Note to physicians	Treat symptomatically.	
4.4. Reference to Other Sections		
Reference to Other Sections	See Section 12: ECOLOGICAL INFORMATION. Section 7: HANDLING AND STORAGE. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.	
Section 5: FIRE-FIGHTING MEASURES		

5.1. Extinguishing media

Suitable Extinguishing Media Use CO2, dry chemical, or foam.

BOSTIK WALLBOARD GOLD ADHESIVE

Unsuitable Extinguishing Media No information available.

5.2. Special hazards arising from the substance or mixture

Specific Hazards Arising from the Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). **Chemical**

5.3. Advice for firefighters

Special Protective Equipment for Wear self contained breathing apparatus for fire fighting if necessary. **Fire-fighters**

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas.
OTHER INFORMATION	Water spray may reduce vapor; but may not prevent ignition in closed spaces.
For Emergency Responders	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
6.2. Environmental precautions	
Environmental Precautions	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
6.3. Methods and material for con	tainment and cleaning up_
Methods for Containment	Dike far ahead of spill; use dry sand to contain the flow of material. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).
Methods for Cleaning up	Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.
6.4. Reference to other sections	
Reference to Other Sections	See Section 12: ECOLOGICAL INFORMATION Section 7: HANDLING AND STORAGE Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on Safe Handling	Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take precautionary measures against static charges. Use explosion-proof electrical/ventilating/lighting/equipment.
7.2. Conditions for safe storage, in	ncluding any incompatibilities
General Hygiene Considerations	Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.
Storage Conditions	Keep only in the original container/package in a cool well-ventilated place. Protect from moisture.
Incompatible Materials	Strong acids and bases

BOSTIK WALLBOARD GOLD ADHESIVE

Version 2

7.3. Specific end use(s)

OTHER INFORMATION

No information available.

7.4. References to Other Sections

Reference to Other Sections

See Section 12: ECOLOGICAL INFORMATION. Section 7: HANDLING AND STORAGE. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Chemical Name	New Zealand	Australia	European Union
Toluene	TWA: 50 ppm	50 ppm	TWA: 50 ppm
108-88-3	TWA: 188 mg/m ³	191 mg/m ³	TWA: 192 mg/m ³
	Skin	150 ppm STEL	STEL: 100ppm
		574 mg/m ³ STEL	STEL: 384mg/m ³
			S*
Cyclohexane	TWA: 100 ppm	100 ppm	TWA: 200 ppm
110-82-7	TWA: 350 mg/m ³	350 mg/m ³	TWA: 700 mg/m ³
	STEL: 300 ppm	300 ppm STEL	
	STEL: 1050 mg/m ³	1050 mg/m ³ STEL	
Zinc oxide	TWA: 10 mg/m ³	10 mg/m ³	-
1314-13-2	TWA: 3 mg/m ³	5 mg/m ³	
	STEL: 10 mg/m ³	10 mg/m ³ STEL	
Hexane	TWA: 20 ppm	20 ppm	TWA: 20 ppm
110-54-3	TWA: 72 mg/m ³	72 mg/m ³	TWA: 72 mg/m ³

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL
Toluene	TWA: 20 ppm	IDLH: 500 ppm	TWA: 200 ppm
108-88-3		TWA: 100 ppm	Ceiling: 300 ppm
		TWA: 375 mg/m ³	
		STEL: 150 ppm	
		STEL: 560 mg/m ³	
Cyclohexane	TWA: 100 ppm	IDLH: 1300 ppm	TWA: 300 ppm
110-82-7		TWA: 300 ppm	TWA: 1050 mg/m ³
		TWA: 1050 mg/m ³	-
Zinc oxide	STEL: 10 mg/m ³ respirable	IDLH: 500 mg/m ³	TWA: 5 mg/m ³ fume
1314-13-2	particulate matter	Ceiling: 15 mg/m ³ dust	TWA: 15 mg/m ³ total dust
	TWA: 2 mg/m ³ respirable	TWA: 5 mg/m ³ dust and fume	TWA: 5 mg/m ³ respirable fraction
	particulate matter	STEL: 10 mg/m ³ fume	
Hexane	TWA: 50 ppm	IDLH: 1100 ppm	TWA: 500 ppm
110-54-3	S*	TWA: 50 ppm	TWA: 1800 mg/m ³
		TWA: 180 mg/m ³	-

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available (PNEC)

OTHER INFORMATION No information available

8.2. Exposure controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas.

PPE - Personal Protection Equipment

Eye/Face Protection	Wear safety glasses with side shields (or goggles).
Skin and Body Protection	Wear suitable protective clothing. No special technical protective measures are
-	necessary under normal conditions.

BOSTIK WALLBOARD GOLD ADHESIVE Version 2

Wear suitable chemical resistant gloves. The selection of suitable gloves does not only
depend on the material, but also on further marks of quality and various manufacturers.
No protective equipment is needed under normal use conditions. Respiratory protection
required in insufficiently ventilated working areas and during spraying. An air-fed mask,
or for short periods of work, a combination of professional filter is recommended.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after
handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and
wash before reuse.

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Color Odor Odor Threshold

Property pН **Melting Point/Freezing Point Boiling Point Flash Point Evaporation Rate** Flammability (solid, gas) Flammability Limit in Air **Upper Flammability Limit** Lower Flammability Limit Vapor Pressure Vapor Density **Relative Density** Water Solubility **Solubility in Other Solvents Partition Coefficient Autoignition Temperature Decomposition Temperature Kinematic Viscosity Dynamic Viscosity Explosive Properties Oxidizing Properties**

9.2. Other information Softening Point Molecular Weight Solvent Content (%) Solid Content (%) Density Bulk Density VOC Very viscous Liquid Yellow Solvent No information available

<u>Values</u> No information available No information available > 50 °C / 122 °F -20 °C / -4 °F No information available No information available

7.2 1.2 No information available No information available 0.99 Insoluble in water No information available No information available

No information available No information available No information available approx 45 0.99 g/cm³ No information available > 500 g/L Remarks • Method Not applicable

Not applicable

CC (closed cup)

Not applicable for liquids

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity

Stable under recommended storage conditions.

10.2. Chemical Stability

Stability

Stable under recommended storage conditions

10.3. Possibility of Hazardous Reactions

BOSTIK WALLBOARD GOLD ADHESIVE Version 2

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization	None under normal processing.	
10.4. Conditions to Avoid		
Conditions to Avoid	Keep away from heat, sparks and flames. Protect from moisture.	
10.5. Incompatible Materials		
Incompatible Materials	Strong acids and bases.	
10.6. Hazardous Decomposition Products		
Hazardous Decomposition Products	Carbon oxides.	

Section 11: TOXICOLOGY INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity

Product Information	Product does not present an acute toxicity hazard based on known or supplied information.
Inhalation	No Data Available.
Eye contact	No Data Available.
Skin Contact	No Data Available.
Ingestion	No Data Available.

Numerical measures of toxicity

Unknown acute toxicity

8.7934 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
20.67594 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
30.80894 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
31.88744 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
31.88744 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene 108-88-3	= 5580 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	> 20 mg/L (Rat)4 h
Cyclohexane 110-82-7	= 12705 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 13.9 mg/L (Rat)4 h
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	LD50 >2000 mg/Kg (Rat) (OECD 402)	LC50 (4h) >5.7 mg/l
Tall oil rosin 8052-10-6	= 7600 mg/kg(Rat)	-	-
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat)4 h
4-tert-Butylphenol 98-54-4	= 4000 mg/kg(Rat)	LD50 >5000 mg/kg (rabbit) OECD 402	-

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Skin Corrosion/Irritation	No information available.
Serious Eye Damage/Eye Irritation	No information available.
Sensitization	No information available.
Germ Cell Mutagenicity	No information available.
Reproductive Toxicity	Product is or contains a chemical which is a known or suspected reproductive hazard.
STOT - Single Exposure	No information available.
STOT - Repeated Exposure	No information available.
Target Organ Effects	Central nervous system, Eyes, Kidney, Liver, Respiratory system, Skin.
Aspiration Hazard	No information available.

BOSTIK WALLBOARD GOLD ADHESIVE

Version 2

Carcinogenicity

No information available.

Chemical Name	IARC	China	Japan
Toluene	Group 3	-	-
IARC (International Agency for Research on Cancer)	Group 3 - Not Classifiable as to Carcinogenicity in Humans Group 2B - Possibly Carcinogenic to Humans		

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity

Product Information

Toxic to aquatic life with long lasting effects. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/Aquatic Plants	Fish	Crustacea
Toluene	EC50 72 h = 12.5 mg/L	LC50 96 h 5.89 - 7.81 mg/L	EC50 48 h 5.46 - 9.83 mg/L
108-88-3	(Pseudokirchneriella subcapitata)	(Oncorhynchus mykiss	(Daphnia magna Static) EC50 48 h
100-00-3		flow-through) LC50 96 h = 5.8	= 11.5 mg/L (Daphnia magna)
		mg/L (Oncorhynchus mykiss	
		semi-static)	
Cyclohexane	EC50 72 h > 9.3 mg/L	LC50 96 h 23.03 - 42.07 mg/L	EC50 24 h > 400 mg/L (Daphnia
110-82-7	(Pseudokirchnerella subcapitata)	(Pimephales promelas static) LC50	
110 02 1	(i seddekirerinerena saboapitata)	96 h 48.87 - 68.76 mg/L (Poecilia	magna)
		reticulata static) LC50 96 h 3.96 -	
		5.18 mg/L (Pimephales promelas	
		flow-through) LC50 96 h 24.99 -	
		44.69 mg/L (Lepomis macrochirus	
		static)	
Zinc oxide	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L Fish (Danio	LC 50 (48Hr) =0.5 mg/l
1314-13-2		rerio)	(Ceriodaphnia dubia)
Tall oil rosin	EC50 72 h 185 - 217 mg/L	LC50 96 h 100 - 200 mg/L	EC50 48 h 238 - 479 mg/L
8052-10-6	(Pseudokirchneriella subcapitata)	(Brachydanio rerio static)	(Daphnia magna)
Hexane	-	LC50 96 h 2.1 - 2.98 mg/L	EC50 24 h > 1000 mg/L (Daphnia
110-54-3		(Pimephales promelas	magna)
		flow-through)	ů,
4-tert-Butylphenol	EC50 72 h = 11.2 mg/L	LC50 96 h 4.71 - 5.62 mg/L	EC50 48 h 3.4 - 4.5 mg/L
98-54-4	(Desmodesmus subspicatus)	(Pimephales promelas	(Daphnia magna Static) EC50 48 h
		flow-through) LC50 96 h = 6.9	= 3.9 mg/L (Daphnia magna)
		mg/L (Cyprinus carpio static)	

12.2. Persistence and Degradability

No information available.

12.3. Bioaccumulative Potential

No information available.

12.4. Mobility in Soil

No information available.

12.5. Results of PBT and vPvB Assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other Adverse Effects

No information available. Endocrine Disruptor

BOSTIK WALLBOARD GOLD ADHESIVE

Version 2

Information

Chemical Name	EU - Endocrine Disrupters	EU - Endocrine Disruptors -	Endocrine disrupting potential
4-tert-Butylphenol	Candidate List Group II Chemical	Evaluated Substances	<u> </u>
Section 13: DISPOSAL C	ONSIDERATIONS		
13.1. Waste Treatment Method	<u>s</u>		
Waste from Residues/Unused Products	Disposal should be in acc regulations.	cordance with applicable regiona	al, national and local laws and
Contaminated Packaging	Improper disposal or reus	se of this container may be dang	perous and illegal.
Section 14: TRANSPORT	ATION INFORMATION		
IMDG UN/ID No Proper Shipping Name Hazard Class Packing Group EmS-No Special Provisions Limited Quantity (LQ) Description	UN1133 Adhesives 3 III F-E, S-D 223, 955 5 L UN1133, Adhesives, 3, I	II, (-20°C c.c.)	
IATA UN/ID No Proper Shipping Name Hazard Class Packing Group ERG Code Limited Quantity (LQ) Special Provisions Description	UN1133 Adhesives 3 III 3L 10 L A3 UN1133, Adhesives, 3, I	11	
ADR UN/ID No Proper Shipping Name Hazard Class Hazard Labels Packing Group Description Environmental Hazard Limited Quantity (LQ) Special Provisions Classification Code Tunnel Restriction Code	UN1133 Adhesives, Environmenta 3 3 III UN1133, Adhesives, Env yes 5 L 640E F1 (D/E)	ally Hazardous vironmentally Hazardous, 3, III, ((D/E)

Section 15: REGULATORY INFORMATION

National Regulations

Section 16: OTHER INFORMATION

Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet No information available

Key Literature References and Sources for Data

BOSTIK WALLBOARD GOLD ADHESIVE	
Version 2	

Revision Date 19-Apr-2017 Supersedes Date: 05-Sep-2016

No information available

Prepared By	Product Safety & Regulatory Affairs
Revision Date	19-Apr-2017
Revision Note	Not applicable.
Training Advice	Provide adequate information, instruction, and training for operator

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet