

## ALL ALUMINIUM SEMI-SEALED ROOFING AND CLADDING RIVETS

AT LAST! A FOOL-PROOF, EASY TO USE, ALL ALUMINIUM 4mm SEMI-SEALED, MULTI GRIP RIVET FOR FIXING FLASHINGS AND 100 OTHER USES IN THE ROOFING INDUSTRY!

FEATURES	BENEFITS
4mm body	Same sized body as before
Pre-drill 4.1mm pilot hole	Ability to use the same drill bits
Aluminium mandrel	No rusting if dropped or left on a roof or in a gutter
Stem locking system	Eliminates the risk of mandrel head vibrating loose, while providing increased strength and a weather resistant joint
Grip range 1.2mm – 4.8mm	Works well with multiple material thicknesses Reduces inventories and eliminates operator error
Shear strength = 845N	Same strength as old system
Tensile strength = 1025N	Same strength as old system
Soft set system	Easy to pull up and set correctly
No touch up paint needed!	27 Common colours available ex-stock
Bulbing formation	Will fit oversize or irregular holes, providing extra strength and vibration resistance
Semi sealed body	No need to place silicone on rivet head once set

### SPECIFICATIONS

GRIP RANGE (L)	HEAD DIAMETER (H)	HEAD THICKNESS (T)	STANDARD STRENGTH N (NOM.)	
			SHEAR	TENSILE
1.2 – 4.8mm	7.9mm	1.27mm	1000	1600

